



Type code		Displacement cm ³ /rev	Dimensions								Weight Kg
					Inlet			Outlet			
			A	B	d ₁	g ₁	d ₃	d ₄	d ₂	g ₂	
PRD2-211D	PRD2-211S	4	41.3	86.7	15	M6	30.2	30.2	15	M6	2.8
PRD2-212D	PRD2-212S	5.5	42.5	89.2	15	M6	30.2	30.2	15	M6	2.85
PRD2-213D	PRD2-213S	8	44.6	93.3	15	M6	30.2	30.2	15	M6	2.9
PRD2-214D	PRD2-214S	11	48.5	98.3	20	M8	39.7	30.2	15	M6	3.0
PRD2-214D-15	PRD2-214S-15	11	48.5	98.3	13.5	M6	30.2	30.2	13.5	M6	3.0
PRD2-214D30x30	PRD2-214S 30x30	11	48.5	98.3	15	M6	30.2	30.2	15	M6	3.0
PRD2-215D	PRD2-215S	14	49	103.3	20	M8	39.7	30.2	15	M6	3.2
PRD2-215D-15	PRD2-215S-15	14	49	103.3	15	M6	30.2	30.2	15	M6	3.2
PRD2-215D40x40	PRD2-215S 40x40	14	49	103.3	20	M8	39.7	39.7	15	M8	3.2
PRD2-216D	PRD2-216S	16	49	106.7	20	M8	39.7	30.2	15	M6	3.4
PRD2-216D-15	PRD2-216S-15	16	49	106.7	15	M6	30.2	30.2	15	M6	3.4
PRD2-216D40x40	PRD2-216S 40x40	16	49	106.7	20	M8	39.7	39.7	20	M8	3.4
PRD2-217D	PRD2-217S	19	49	111	20	M8	39.7	30.2	15	M6	3.6
PRD2-217D-60	PRD2-217S-60	19	60	111	20	M8	39.7	30.2	15	M6	3.6
PRD2-218D	PRD2-218S	22.5	56.5	117	20	M8	39.7	30.2	15	M6	3.8
PRD2-219D	PRD2-219S	26	60	123	22	M8	39.7	30.2	15	M6	4.0

